



Specification:

- 1. Connector Type : SC/PC Multimode
- 2. Cable Type :
Zipcord cable, $\varnothing 3.0\text{mm}$, 50/125um Multimode,
Cable Jacket : Orange color, PVC material
- 3. Length : xM
- 4. Cable Marker
- 5. Shrink Tube

Performance:

- a. Insertion Loss : $< 0.5 \text{ dB}$
- b. Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. Ferrule End-face Radius : $10 < R < 30\text{mm}$
- d. Apex Offset : $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating : 0.2 dB Max.
- f. Operation Temperature : $-20^\circ \text{ to } +70^\circ$
- g. Storage Temperature : $-40^\circ \text{ to } +80^\circ$
- h. Humidity (non-condensing) 95%RH

BELKIN®

BELKIN CORPORATION
 501 West Walnut Street, Compton, CA 90220-5221, USA
 TEL: 310-898-1100; FAX: 310-898-1111
 www.belkin.com

PART NO.: A2F40277

DES.: SC to SC Duplex patch cord

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>