



HOTSOAK 51


HOTSOAK SERIES MODEL # AI7236RHS














Rough-In Plumbing

SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size 71 1/2" x 36 1/4" x 23 1/4" 182 cm x 92 cm x 59 cm

48 1/2" long

Bathing Well 24" wide

21 3/4" interior depth

Shipping Weight 209 lbs. / 95 kg **Tub Weight Filled** 875 lbs. / 395 kg **Tub Only Weight** 126 lbs. / 57 kg

Gallons to Overflow 90 gal. / 341 L

ELECTRICAL SPECIFICATIONS:

Pump 1/15 HP; 1.3 AMP; 110V 1.5 kW; 12.5 AMP; 110V Heater 20 AMP: 110V, separate circuit Requirements required protected w/ Class A GFCI

STANDARD EQUIPMENT:

Aquatic Quality Features:

- 1.5 kW Inline Maintenance Heater
- Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- 2 Color Matched Grab Bars
- 2 Arm Rests
- Slip Resistant Floor
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed, Factory Tested

Limited Lifetime Warranty

- · Chromatherapy LED Lighting*
- Comfort Pillow Oval or Rectangle

OPTIONAL EQUIPMENT:

- - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Factory Installed Rigid ABS Tile Flange
- **Optional Pump Location**
- Color Matched Acrylic Skirt
- **Premium Colors**

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

Fax-On-Demand Document #1226

August 2008



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub: Aquatic Industries, Inc. assumes no responsibility for preparatory work. www.aguaticwhirlpools.com 800.555.5324

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com