
Operation Guide 4755

CASIO®



• To set the time

- Pull the crown out when the second hand is at 12 o'clock position and the second hand
- stops.

 2. Set the hands by rotating the crown. Rotate the crown to move the hands. Move the B move the hands. Move the minute hand four or five minutes past the time you want to set, and then back it up to the proper setting.

 3. Push the crown back in to the normal position.

Using the Stopwatch



The stopwatch lets you measure elapsed time up to 11 hours, 59 minutes, 59 seconds

To measure times with the stopwatch




To adjust the positions of the stopwatch second hand

- Press
 to reset the stopwatch, and check the alignment of the stopwatch minute hand and second hand.
- 2. Pull out the crown
- 2. Full of the common states and the stopward second hand forward until it points to the 12 o'clock position.

 4. Push the crown back in to its normal position.

■ For a watch with an elapsed time bezel





- Some water resistant models are equipped with a screw lock
- Some water resistant models are equipped with a screw loc crown.
 With such models, you must unscrew the crown in the direction noted in the illustration to loosen it before you can pull it out. Do not pull too forcibly on such crowns.
 Also note that such watches are not water resistant while
- their crowns are loosened. Be sure to screw the crowns back in as far as they will go after making any setting.



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com